

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE	—	26/07/12	M. Dong

TECHNICAL DATA

Electrical

Impedance	50 Ω
Frequency range	0~50 GHz
VSWR	1.15:1
Contact resistance	
-centre contact	≤3mΩ
-outer contact	≤2mΩ
Insulation resistance	≥3000MΩ

Mechanical & Environmental


Durability (matings)	>500
Temperature range	-55 °C ~ +165 °C
RoHS Compliant	Yes

Material & Finish


Body	Stainless Steel (SU303), Passivated
Pin Contact	Beryllium Copper Alloy, Gold-plated
Insulator	PEI

Interface Standards

2.4mm	IEEE STD 287-2007
-------	-------------------



Part Number	D	L
C11214027A	0.75 [.029]	9 [.354]
C11214027B	0.86 [.034]	8.75 [.344]
C11214027C	1 [.040]	5.5 [.216]
C11214027D	1.04 [.041]	6.34 [.250]
C11214027E	1.2 [.047]	3 [.118]



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

DRAWN:	W. Shen	26/07/12
CHECKED:	K. Liu	26/07/12
APPROVED:	M. Dong	26/07/12
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS [INCHES]. UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: .XX ±0.13 [.005"] .X ±0.20 [.008"] X ±0.50 [.019"] ANGULAR TOLERANCES ARE: ALL=±1°		

TITLE:
2.4mm Straight Female,
Air Line Through the Wall,
2 Hole Flange

CONNNOV
www.connov.com

PART No.:
C11214027

DO NOT SCALE
DRAWING

PROJECTION:

SIZE: A4
SCALE: 4:1
SHEET: 1/1
REV: A