

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE		21/07/12	M. Dong

TECHNICAL DATA

Electrical

Impedance	50 Ω
Frequency range	0~65 GHz
VSWR	1.25:1
Contact resistance	
-centre contact	$\leq 3\text{m}\Omega$
-outer contact	$\leq 2.5\text{m}\Omega$
Insulation resistance	$\geq 3000\text{M}\Omega$

Mechanical & Environmental


Durability (matings)	>500
Temperature range	-55 °C ~ +165 °C
RoHS Compliant	Yes

Material & Finish


Body	Stainless Steel (SU303), Passivated
Pin Contact	Beryllium Copper Alloy, Gold-plated
Insulator	PEI

Interface Standards

1.85mm	IEC-61169
--------	-----------



Part Number	ØD PIN
C10114008A	0.23 [0.009]
C10114008B	0.30 [0.012]



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

DRAWN:	W. Shen	21/07/12	TITLE: 1.85mm Straight Male, 2 Hole Flange, Accepts Pin		 www.connov.com							
CHECKED:	K. Liu	21/07/12										
APPROVED:	M. Dong	21/07/12										
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS [INCHES]. UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: .XX±0.13 [0.005] .X±0.20 [0.008] X±0.50 [0.019]			DO NOT SCALE DRAWING PROJECTION:		PART No.: C10114008							
ANGULAR TOLERANCES ARE: ALL=±1°					SIZE: A4		SCALE: 4:1		SHEET: 1/1		REV: A	