

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE		02/08/12	M. Dong

TECHNICAL DATA

Electrical

Impedance	50 Ω
Frequency range	0~27 GHz
VSWR	1.10:1 (DC to 18GHz)
	1.15:1 (18GHz to 27GHz)

Contact resistance

-centre contact	$\leq 3\text{m}\Omega$
-outer contact	$\leq 2\text{m}\Omega$
Insulation resistance	$\geq 5000\text{M}\Omega$

Mechanical & Environmental


Durability (matings)	>500
Temperature range	-55 °C ~ +165 °C
RoHS Compliant	Yes

Material & Finish


Body	Stainless Steel (SU303), Passivated
Pin Contact	Beryllium Copper Alloy, Gold-plated
Insulator	PTFE

Interface Standards

SMA	MIL-STD-348A
-----	--------------



Part Number	ØD PIN
C14214001A	0.23 [.009]
C14214001B	0.30 [.012]
C14214001C	0.38 [.015]
C14214001D	0.46 [.018]
C14214001E	0.51 [.020]



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

DRAWN:	W. Shen	02/08/12	TITLE: SMA Straight Female, 4 Hole Flange, Accept Pin		 www.connov.com									
CHECKED:	K. Liu	02/08/12												
APPROVED:	M. Dong	02/08/12			PART No.: C14214001									
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS [INCHES]. UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: .XX ±0.13 [.005] .X ±0.20 [.008] X ±0.50 [.019]			DO NOT SCALE DRAWING		PROJECTION: 		SIZE:		SCALE:		SHEET:		REV:	
ANGULAR TOLERANCES ARE: ALL ±1°							A4		4:1		1/1		A	